



Where innovative ideas take hold.

**#140**  
**10 mil White PVC Tape**  
**Product Information**

**PRODUCT DESCRIPTION**

**Principal Uses:**

Compac #140 PVC tape is used for sealing PVC jacketing and fitting covers on mechanical insulation systems.

**Features/Benefits:**

Compac #140 tape provides a matching appearance and vapor seal for PVC jacketing and fitting covers.

Please contact Technical Service for help with product and application questions at 877-5COMPAC (1-877-526-6722).

TECHNICAL INFORMATION	TEST METHOD	VALUE
Substrate (Backing)	Visual, Micrometer	10 mil White PVC
Adhesive	Infrared Analysis	Rubber Based
Liner	Visual	None
Thickness without Liner	PSTC 33/ASTM D 3652	10 mils      0.25 mm
Peel Adhesion to Steel	PSTC 1/ASTM D 3330	14 oz/in      0.2 kN/m
Tensile Strength	PSTC 31/ASTM D 3759	16 lb/in      0.45 kN/m
Elongation	PSTC 31/ASTM D 3759	300%

The listed values are typical, and not intended to serve as product specifications. Weights and thicknesses are nominal, +/-10%.

**Application and Storage:**

Surface to which tape will be applied must be clean and dry, and free of contaminants. Apply pressure with plastic squeegee. Ideal storage conditions are 60°F to 80°F (16°C to 27°C), with low humidity.

Sheet No.:PIS-610

Revision No.: 0.0

Date: 07/29/05

