



Where innovative ideas take hold.

#150
Filament Strapping Tape
Product Information

PRODUCT DESCRIPTION

Principal Uses:

Compac #150 filament strapping tape is used as a temporary support for pipe insulation during installation. Also has various non-insulation uses for packaging and restraining.

Features/Benefits:

Compac #150 has good adhesion and tensile strength, and is abrasion and split resistant.

Please contact Technical Service for help with product and application questions at 877-5COMPAC (1-877-526-6722).

TECHNICAL INFORMATION	TEST METHOD	VALUE	
Substrate (Backing)	Visual	Filament Reinforced Poly	
Adhesive	Infrared Analysis	Rubber Based	
Liner	Visual	None	
Thickness without Liner	PSTC 33/ASTM D 3652	4.5 mils	0.11 mm
Peel Adhesion to Steel	PSTC 1/ASTM D 3330	48 oz/in	0.5 kN/m
Tensile Strength	PSTC 31/ASTM D 3759	180 lb/in	31.5 kN/m
Elongation	PSTC 31/ASTM D 3759	5%	

The listed values are typical, and not intended to serve as product specifications. Weights and thicknesses are nominal, +/-10%.

Application and Storage:

Surface to which tape will be applied must be clean and dry, and free of contaminants. Apply pressure with plastic squeegee. Ideal storage conditions are 60°F to 80°F (16°C to 27°C), with low humidity.

Sheet No.:PIS-611

Revision No.: 0.0

Date: 07/29/05

