



Where innovative ideas take hold.

#164
Professional /
Contractor Grade
Duct Tape
Product Information

PRODUCT DESCRIPTION

Principal Uses:

Compac #164 is used in motorsports, silk screening, plastering, stucco masking, HVAC dust systems, bundling, seaming, sealing and splicing.

Features/Benefits:

Compac #164 has a waterproof backing and is highly conformable, with an aggressive adhesive having excellent tack and easy unwind. It can be used for indoor and outdoor applications.

Available Colors: Silver, Black, and Red

Please contact Technical Service for help with product and application questions at 1-877-5COMPAC (1-877-526-6722).

TECHNICAL INFORMATION	TEST METHOD	VALUE
Substrate (Backing)	Visual	Polyethylene film and polyester/cotton blend cloth
Adhesive	Infrared Analysis	Natural Rubber
Adhesion to Steel	PSTC-1 ASTM D3330	55 oz./in (61N/100mm)
Quick stick to Steel	PSTC-5	18 oz/in (20N/100mm)
Tensile Strength	PSTC-31 ASTM D3759	40 lbs/in (704N/100mm)
Elongation	PSTC-31 ASTM D3759	10%
Thickness	PSTC-33 ASTM D3652	12.5 mils (0.31 mm)
Maximum service temperature	Oven Exposure	200°F (93°C)

Application and Storage:

Surface to which tape will be applied must be clean and dry, and free of contaminants. Apply pressure with plastic squeegee. Ideal storage conditions are 60°F to 80°F (16°C to 27°C), with low humidity.

This Product Information Sheet is not intended to serve as a specification for the product; for purposes of setting specification requirements, prior agreement between Compac and the user must be established. Some values shown herein are based on measures of central tendency, and as such are considered typical or average results. Other statistical measures may be employed to determine minimum or maximum specification values. No warranty is expressed or implied with the information contained herein. Please review Compac Terms and Conditions of Sale for further information.