



**#172
General Purpose
Masking Tape
Product Information**

Where innovative ideas take hold.

PRODUCT DESCRIPTION

Principal Uses:

Compac #172 is a general purpose masking tape which provides excellent adhesion to a wide variety of surfaces in a wide range of applications including light bundling, packaging and light duty masking use.

Features/Benefits:

- Clean removal from most surfaces
- Conforms well to irregular surfaces
- Adheres well to a variety of substrates
- Economically priced

Please contact Technical Service for help with product and application questions at 1-877-5COMPAC (1-877-526-6722).

TECHNICAL INFORMATION	TEST METHOD	VALUE
Substrate (Backing)	Visual	Crepe Paper
Adhesive	Infrared Analysis	Rubber
Adhesion to Steel	PSTC-1 ASTM D3330	33 oz./in (36N/100mm)
Tensile Strength	PSTC-31 ASTM D3759	16 lbs/in (282N/100mm)
Elongation	PSTC-31 ASTM D3759	7%
Thickness	PSTC-33 ASTM D3652	5.0 mils (0.13 mm)
Maximum service temperature	Oven Exposure	140°F (60°C)

Application and Storage:

Surface to which tape will be applied must be clean and dry, and free of contaminants. Apply pressure with plastic squeegee. Ideal storage conditions are 60°F to 80°F (16°C to 27°C), with low humidity.

This Product Information Sheet is not intended to serve as a specification for the product; for purposes of setting specification requirements, prior agreement between Compac and the user must be established. Some values shown herein are based on measures of central tendency, and as such are considered typical or average results. Other statistical measures may be employed to determine minimum or maximum specification values. No warranty is expressed or implied with the information contained herein. Please review Compac Terms and Conditions of Sale for further information.