



Where innovative ideas take hold.

**#200**  
**Embossed White Vinyl Tape**  
**UL Classified**

**Product Information**

**PRODUCT DESCRIPTION**

**Principal Uses:**

Compac #200 white embossed vinyl tape is used for seam sealing and patching of white vinyl faced metal building and duct wrap insulation, and other insulation applications where white vinyl facing is used.

**Features/Benefits:**

Compac #200 tape features an aggressive acrylic adhesive that bonds tightly and permanently when smoothed down on the insulation facing surface.

Please contact Technical Service for help with product and application questions at 877-5COMPAC (1-877-526-6722).

TECHNICAL INFORMATION	TEST METHOD	VALUE	
Substrate (Backing)	Visual	Embossed White Vinyl	
Adhesive	Infrared Analysis	Acrylic	
Liner	Visual	Kraft	
Thickness without Liner	PSTC 33/ASTM D 3652	4.3 mils	0.10 mm
Peel Adhesion to Steel	PSTC 1/ASTM D 3330	40 oz/in	0.4 kN/m
Tensile Strength	PSTC 31/ASTM D 3759	10 lb/in	1.8 kN/m
Elongation	PSTC 31/ASTM D 3759	70%	
Surface Burning Characteristics	UL 723/ASTM E 84 UL File No. R6131	5 flame	10 smoke

The listed values are typical, and not intended to serve as product specifications. Weights and thicknesses are nominal, +/-10%.

**Application and Storage:**

Surface to which tape will be applied must be clean and dry, and free of contaminants. Apply pressure with plastic squeegee. Ideal storage conditions are 60°F to 80°F (16°C to 27°C), with low humidity.

Sheet No.:PIS-612

Revision No.: 0.0

Date: 07/29/05

