



Where innovative ideas take hold.

**#225
VRV Tape**

Product Information

PRODUCT DESCRIPTION

Principal Uses:

Compac #225 VRV (Vinyl-Reinforcement-Vinyl) tape is used for seam sealing and patching of VRV faced metal building insulation, and other insulation applications where VRV facing is used.

Features/Benefits:

Compac #225 tape features an aggressive acrylic adhesive that bonds tightly and permanently when smoothed down on the insulation facing surface. AW adhesive technology permits service temperatures of 0°F to 150°F (-18°C to 66°C), and an application range of 10°F to 120°F (-12°C to 49°C).

Please contact Technical Service for help with product and application questions at 877-5COMPAC (1-877-526-6722).

TECHNICAL INFORMATION	TEST METHOD	VALUE	
Substrate (Backing)	Visual	VRV Facing	
Adhesive	Infrared Analysis	Acrylic	
Liner	Visual	Kraft	
Thickness without Liner	PSTC 33/ASTM D 3652	6.0 mils	0.15 mm
Peel Adhesion to Steel	PSTC 1/ASTM D 3330	63 oz/in	0.7 kN/m
Tensile Strength	PSTC 31/ASTM D 3759	18 lb/in	3.2 kN/m
Elongation	PSTC 31/ASTM D 3759	40%	

The listed values are typical, and not intended to serve as product specifications. Weights and thicknesses are nominal, +/-10%.

Application and Storage:

Surface to which tape will be applied must be clean and dry, and free of contaminants. Apply pressure with plastic squeegee. Ideal storage conditions are 60°F to 80°F (16°C to 27°C), with low humidity.

Sheet No.:PIS-614

Revision No.: 0.0

Date: 07/29/05

