



Where innovative ideas take hold.

**#229**  
**Metalized Polyester**  
**All Service Jacket (ASJ) Tape**  
**UL Classified**

**Product Information**

**PRODUCT DESCRIPTION**

**Principal Uses:**

Compac #229 ASJ insulation tape is used for seam sealing and patching of ASJ-faced mechanical insulation systems, providing a matching appearance and vapor retarder integrity.

**Features/Benefits:**

Compac #229 tape features an aggressive, all-weather acrylic adhesive that bonds tightly and permanently when smoothed down on the insulation facing surface. AW adhesive technology permits service temperatures of 0°F to 150°F (-18°C to 66°C), and an application range of 10°F to 120°F (-12°C to 49°C).

Please contact Technical Service for help with product and application questions at 877-COMPAC (1-877-526-6722).

TECHNICAL INFORMATION	TEST METHOD	VALUE	
Substrate (Backing)	ASTM C 1136	ASJ, Meets Type I - IV	
Adhesive	Infrared Analysis	Acrylic	
Liner	Visual	Kraft	
Thickness without Liner	PSTC 33/ASTM D 3652	11 mils	0.28 mm
Peel Adhesion to Steel	PSTC 1/ASTM D 3330	96 oz/in	1.05 kN/m
Tensile Strength	PSTC 31/ASTM D 3759	50 lb/in	8.8 kN/m
Elongation	PSTC 31/ASTM D 3759	1%	
Permeance	ASTM E 96, Procedure A	0.02 perm	1.15 ng/m <sup>2</sup> ·s·Pa
Surface Burning Characteristics	UL 723/ASTM E 84 UL File No. R6131	5 flame	5 smoke

The listed values are typical, and not intended to serve as product specifications. Weights and thicknesses are nominal, +/-10%.

**Application and Storage:**

Surface to which tape will be applied must be clean and dry, and free of contaminants. Apply pressure with plastic squeegee. Ideal storage conditions are 60°F to 80°F (16°C to 27°C), with low humidity.

Sheet No.:PIS-615

Revision No.: 0.0

Date: 07/29/05

