



Where innovative ideas take hold.

**#351
SSL Tape
Fiber Reinforced Adhesive
UL Classified
Product Information**

PRODUCT DESCRIPTION

Principal Uses:

Compac #351 SSL (Self-Seal Lap) tape is used to seal vapor retarder or facing overlap seams on mechanical and other types of insulation. It can also be used to apply patches or to hang vapor retarders or facings on structural members, and has many general non-insulation uses.

Features/Benefits:

Compac #351 tape features an aggressive, all-weather acrylic adhesive that bonds tightly and permanently when smoothed down on the insulation facing surface. AW adhesive technology permits service temperatures of -30°F to 200°F (-34°C to 93°C), and an application range of 0°F to 130°F (-18°C to 54°C). An easy-lift dry edge is manufactured into the pressure sensitive tape for quick and easy installation.

Please contact Technical Service for help with product and application questions at 877-5COMPAC (1-877-526-6722).

TECHNICAL INFORMATION	TEST METHOD	VALUE	
Adhesive	Infrared Analysis	Fiber Reinforced Acrylic	
Liner	Visual	5.5 mil Kraft	
Thickness without Liner	PSTC 33/ASTM D 3652	2.5 mils	0.06 mm
Peel Adhesion to Steel	PSTC 1/ASTM D 3330	80 oz/in	0.9 kN/m
Surface Burning Characteristics	UL 723/ASTM E 84 UL File No. R6131	5 flame	0 smoke

The listed values are typical, and not intended to serve as product specifications. Weights and thicknesses are nominal, +/-10%.

Application and Storage:

Surface to which tape will be applied must be clean and dry, and free of contaminants. Apply pressure with plastic squeegee. Ideal storage conditions are 60°F to 80°F (16°C to 27°C), with low humidity.

Sheet No.:PIS-624

Revision No.: 0.0

Date: 07/29/05

