



Where innovative ideas take hold.

**#802**  
**3 MIL ALUMINUM**  
**HARNESS WRAP LINERLESS**  
**Pressure Sensitive Tape**  
**Product Information**

**PRODUCT:**

Compac #802 is a 3 mil Aluminum Foil Tape with acrylic adhesive.

**PRINCIPAL USES:**

Compac #802 is specifically designed for economical harness wrap applications. Can also be used for heat reflection, paint masking and duct sealing.

**FEATURES AND BENEFITS:**

Compac #802 is coated with an acrylic adhesive system which creates a superior bond characteristic. The service temperature range is between -30°F (-22°C) to 325°F (163°C).

Please contact Technical Service for help with product and application questions at 877-5COMPAC (1-877-526-6722).

TECHNICAL DATA	TEST METHOD	VALUE
Substrate	Visual	Dead-Soft Aluminum
Adhesive	N/A	Acrylic
Foil Thickness	PSTC-33 ASTM D3652	3.0 mils (0.08mm)
Tape Thickness without Liner	PSTC-33 ASTM D3652	4.5 mils (0.11mm)
Adhesion to Steel	PSTC- 1 ASTM D3330	35 oz/inch (38 N/100mm)
Tensile Strength	PSTC-31 ASTM D3759	28 lbs/inch (490 N/100mm)
Elongation	PSTC-31 ASTM D3759	5.5%

**SURFACE PREPARATION:** The surface to which the tape is applied should be dry, clean, and free of contaminants.

**STORAGE CONDITIONS:** Tape should be stored in a dry area at temperatures of 60°F (16°C) to 80°F (26°C).

**NOTE:** All physical properties listed above have been obtained from random laboratory testing and should not be used for the purpose of writing specifications. THE PRODUCT SHOULD BE TESTED TO DETERMINE THE SUITABILITY FOR ITS INTENDED USE.

Sheet No.:PIS-626

Revision No.:0.0

Date:08/01/05

