



Where innovative ideas take hold.

**#808**  
**2.0 MIL ALUMINUM**  
**GENERAL PURPOSE**  
**Pressure Sensitive Tape**  
**Product Information**

**PRODUCT:**

Compac #808 is a general purpose 2.0 mil Aluminum Foil Tape with liner.

**PRINCIPAL USES:**

Compac #808 dead-soft aluminum foil tape is a general purpose foil used on non-critical applications such as sealing out dust and moisture, masking, and duct sealing.

**FEATURES/BENEFITS:**

Compac #808 aluminum foil is coated with an extremely aggressive acrylic adhesive providing service temperature from 0°F (-18°C) to 150°F (66°C) and application temperatures from 10°F (-12°C) to 120°F (49°C).

Please contact Technical Service for help with product and application questions at 877-5COMPAC (1-877-526-6722).

TECHNICAL DATA	TEST METHOD	VALUE
Substrate	N/A	Dead-Soft Aluminum
Adhesive	N/A	Acrylic (clear)
Foil Thickness	PSTC-33 ASTM D3652	2.0 mils (0.05mm)
Tape Thickness without Liner	PSTC-33 ASTM D3652	3.0 mils (0.08mm)
Adhesion to Steel	PSTC- 1 ASTM D3330	45 oz/inch (50 N/100mm)
Tensile Strength	PSTC-31 ASTM D3759	15 lbs/inch
Elongation	PSTC-31 ASTM D3759	5%
Release Liner	PSTC-33 ASTM D3652	4.0 mils (0.10mm)
Permeance	ASTME-96	0.0 perms
Government Specification	None	None
Flammability	UL510, SECTION 4 File #E130121	Recognized Component

**SURFACE PREPARATION:** The surface to which the tape is applied should be dry, clean, and free of contaminants.

**STORAGE CONDITIONS:** Tape should be stored in a dry area at temperatures of 60°F (16°C) to 80°F (26°C).

**NOTE:** All physical properties listed above have been obtained from random laboratory testing and should not be used for the purpose of writing specifications. **THE PRODUCT SHOULD BE TESTED TO DETERMINE THE SUITABILITY FOR ITS INTENDED USE.**

Sheet No.:PIS-630

Revision No.:0.0

Date:08/01/05

