



Where innovative ideas take hold.

#845
DOUBLE COATED UPVC FILM
ACRYLIC ADHESIVE
PRESSURE SENSITIVE TAPE

Product Information

PRODUCT:

Compac #845 is a Double Coated White UPVC Film pressure sensitive tape with acrylic adhesive.

FEATURES AND BENEFITS:

Compac #845 offers a UPVC film coated with a strong acrylic adhesive. This adhesive tape provides a permanent bond with excellent shear strength. This tape product is highly resistant to plasticizer migration, UV and aging. It exhibits excellent adhesion to a wide variety of substrates, including such hard-to-stick-to substrates as untreated polyethylene, polypropylene, and other low energy surfaces. The product is hand-tearable.

Please contact Technical Service for help with product and application questions at 877-5COMPAC (1-877-526-6722).

TECHNICAL DATA	TEST METHOD	VALUE
Substrate	PSTC-33 ASTM D3652	3.0 mils UPVC Film (0.08mm)
Adhesive	Visual	Acrylic (Clear)
Tape Thickness without Liner	PSTC-33 ASTM D3652	6.0 mils (0.16mm)
Liner Thickness	PSTC-33 ASTM D3652	3.0 mils (0.08mm)
Color	Visual	White
Adhesion to Steel	PSTC- 1 ASTM D3330	100 oz/in (each side) (110N/100mm)
Tensile Strength	PSTC-31 ASTM D3759	15 lbs/in (260N/100mm)
Elongation	PSTC-31 ASTM D3759	200%

SURFACE PREPARATION: The surface to which the tape is applied should be dry, clean, and free of contaminants.

STORAGE CONDITIONS: Tape should be stored in a dry area at temperatures of 60°F (16°C) to 80°F (26°C).

NOTE: All physical properties listed above have been obtained from random laboratory testing and should not be used for the purpose of writing specifications. **THIS PRODUCT SHOULD BE TESTED TO DETERMINE THE SUITABILITY FOR ITS INTENDED USE.**

Sheet No.:PIS-637

Revision No.:0.0

Date:08/01/05

