



Where innovative ideas take hold.

#846
DOUBLE COATED
RUBBER ADHESIVE
PRESSURE SENSITIVE TAPE

Product Information

PRODUCT:

Compac #846 is a Double Coated Polyester Tape with synthetic rubber adhesive.

PRINCIPAL USES:

Compac #846 is used in the bonding of foams, films, plastics and a wide variety of rigid and flexible substrates.

FEATURES/BENEFITS:

Compac #846 is coated with an extremely aggressive, high tack rubber adhesive system. Polyester carrier offers excellent dimensional stability.

Please contact Technical Service for help with product and application questions at 877-5COMPAC (1-877-526-6722).

TECHNICAL DATA	TEST METHOD	VALUE
Substrate	PSTC-33 ASTM D3652	.5 mil Polyester (0.01mm)
Adhesive	N/A	Synthetic Rubber
Tape Thickness without Liner	PSTC-33 ASTM D3652	3.5 mils (0.09mm)
Liner	Weight Per Area	66 lb. Basis Weight
Liner Thickness	PSTC-33 ASTM D3652	4.0 mils
Color	Visual	Transparent
Adhesion to Steel	PSTC- 1 ASTM D3330	100 oz/in (110N/100mm)
Tensile Strength	PSTC-31 ASTM D3759	8 lbs/in
Elongation	PSTC-31 ASTM D3759	10%

SURFACE PREPARATION: The surface to which the tape is applied should be dry, clean, and free of contaminants.

STORAGE CONDITIONS: Tape should be stored in a dry area at temperatures of 60°F (16°C) to 80°F (26°C).

NOTE: All physical properties listed above have been obtained from random laboratory testing and should not be used for the purpose of writing specifications. THE PRODUCT SHOULD BE TESTED TO DETERMINE THE SUITABILITY FOR ITS INTENDED USE.

Sheet No.:PIS-638

Revision No.:0.0

Date:08/01/05

