



Where innovative ideas take hold.

**#852
Double Coated
Tissue Carrier
Pressure Sensitive Tape
Product Information**

PRODUCT DESCRIPTION

Principal Uses:

Compac #852 is a high tack general purpose product generally used for; high speed, splicing applications, holding name plates, fastening and mounting applications, laminating of rigid and flexible substrates, and as a general purpose bonding tape.

Features/Benefits:

Compac #852 tape features an aggressive acrylic adhesive that bonds tightly and permanently when smoothed down on the insulation facing surface. AW adhesive technology permits service temperatures of 0°F to 150°F (-12°C to 66°C), and an application range of 10°F to 120°F (-12°C to 49°C).

Please contact Technical Service for help with product and application questions at 877-5COMPAC (1-877-526-6722).

| TECHNICAL INFORMATION | TEST METHOD | VALUE |
|-------------------------|---------------------|-------------------------|
| Substrate (Carrier) | Visual | Tissue |
| Adhesive | Infrared Analysis | Acrylic |
| Liner | Visual | Kraft |
| Thickness without Liner | PSTC 33/ASTM D 3652 | 4.5 mils 011mm |
| Peel Adhesion to Steel | PSTC 1/ASTM D 3330 | 40 oz/in 0.45 kN/m |
| Tensile Strength | PSTC 31/ASTM D 3759 | 5 lb/in 0.9 kN/m |
| Elongation | PSTC 31/ASTM D 3759 | 1% |

SURFACE PREPARATION: The surface to which the tape is applied should be dry, clean, and free of grease and oil.

STORAGE TEMPERATURE: Tape should be stored in a dry area at temperatures of 60°F to 80°F (16°C to 27°C).

CAUTION: All physical properties listed above have been obtained from random laboratory testing and should not be used for the purpose of writing specifications. THIS PRODUCT SHOULD BE TESTED TO DETERMINE THE SUITABILITY FOR ITS INTENDED USE.

Sheet No.:PIS-641

Revision No.: 0.0

Date: 07/29/05

