



Where innovative ideas take hold.

**#894
DOUBLE COATED
POLYESTER FILM
PRESSURE SENSITIVE TAPE**

Product Information

PRODUCT:

Compac #894 is a Double Coated Polyester Film with acrylic adhesive.

PRINCIPAL USES:

Compac #894 provides excellent adhesion to a wide variety of films and plastics that are used in nameplate and decorative wall applications. Compac #894 also exhibits very good adhesion to a wide variety of foams commonly used in the foam fabricator, gasket manufacturing marketplace.

FEATURES/BENEFITS:

The acrylic adhesive used in #894 is extremely aggressive and offers outstanding adhesion to most plastic surfaces, as well as polyester, polyether and polyethylene foams.

Please contact Technical Service for help with product and application questions at 877-5COMPAC (1-877-526-6722).

TECHNICAL DATA	TEST METHOD	VALUE
Substrate	PSTC-33 ASTM D3652	0.5 mil Polyester Film (0.01mm)
Adhesive	N/A	Acrylic (Clear)
Tape Thickness without Liner	PSTC-33 ASTM D3652	3.5 mils (0.09mm)
Liner Thickness	PSTC-33 ASTM D3652 Weight Per Area	4.0 mils (0.10mm) 60 lb. Basis Weight
Color	Visual	Transparent
Adhesion to Steel	PSTC- 1 ASTM D3330	80 oz/in (each side) (88N/100mm)
Tensile Strength	PSTC-31 ASTM D3759	8 lbs/in (140N/100mm)
Elongation	PSTC-31 ASTM D3759	10%

SURFACE PREPARATION: The surface to which the tape is applied should be dry, clean, and free of contaminants.

STORAGE CONDITIONS: Tape should be stored in a dry area at temperatures of 60°F (16°C) to 80°F (26°C).

NOTE: All physical properties listed above have been obtained from random laboratory testing and should not be used for the purpose of writing specifications. THE PRODUCT SHOULD BE TESTED TO DETERMINE THE SUITABILITY FOR ITS INTENDED USE.

Sheet No.:PIS- 647

Revision No.:0.0

Date:08/01/05

