



Where innovative ideas take hold.

**#900
2 MIL ACRYLIC ADHESIVE
TRANSFER TAPE**

Product Information

PRODUCT:

Compac #900 is a 2 mil Acrylic Transfer Tape.

PRINCIPAL USES:

Compac #900 is an excellent adhesive for flying splices on paper, films, and foil. This product can be used for laminating, mounting and name plate applications, aluminum foil identification plates, and miscellaneous holding.

FEATURES/BENEFITS:

Compac #900 offers a high initial adhesion, and ease of slitting due to fibrous content in adhesive.

Please contact Technical Service for help with product and application questions at 877-5COMPAC (1-877-526-6722).

TECHNICAL DATA	TEST METHOD	VALUE
Substrate	N/A	Acrylic
Tape Thickness without Liner	PSTC-33 ASTM D3652	2.0 mils (0.05mm)
Liner	Weight per area	60# Moisture Stable Liner
Color	Visual	Clear
Adhesion to Steel	PSTC- 1 ASTM D3330	32 oz/inch (35N/100mm)
Low Temperature Application	Temperature Exposure	10°F (-12°C)
High Temperature Resistance	Temperature Exposure	250°F (121°C)
Chemical Resistance (Solvent)	Solvent immersion	Medium-High
Flame Spread*	UL 723/ASTM E-84	5
Smoke Generated*	UL 723/ASTM E-84	0

*UL File No. R6131

SURFACE PREPARATION: The surface to which the tape is applied should be dry, clean, and free of contaminants.

STORAGE CONDITIONS: Tape should be stored in a dry area at temperatures of 60°F (16°C) to 80°F (26°C).

NOTE: All physical properties listed above have been obtained from random laboratory testing and should not be used for the purpose of writing specifications. THE PRODUCT SHOULD BE TESTED TO DETERMINE THE SUITABILITY FOR ITS INTENDED USE.

