



Where innovative ideas take hold.

**#901
ACRYLIC ADHESIVE
TRANSFER TAPE**

Product Information

PRODUCT:

Compac #901 is a 2 mil Acrylic Transfer Tape.

PRINCIPAL USES:

Compac #901 is a higher tack version of #900. This product is suited for joining together materials such as: glass, papers, metals, wood and plastics; and is an excellent adhesive for flying splices on films, paper and foil. It is also used for mounting and nameplate application, aluminum foil identification plates, and miscellaneous holding.

FEATURES/BENEFITS:

Compac #901 offers extremely high adhesion and good shear strength.

Please contact Technical Service for help with product and application questions at 877-5COMPAC (1-877-526-6722).

TECHNICAL DATA	TEST METHOD	VALUE
Substrate	N/A	Acrylic
Tape Thickness without Liner	PSTC-33 ASTM D3652	2.0 mils (0.05mm)
Liner	Weight per area	60# Moisture Stable Liner Silicone Coated Paper
Color	Visual	Clear
Adhesion to Steel	PSTC- 1 ASTM D3330	72 oz/inch (79N/100mm)
Low Temperature Application	Freezer Exposure	10°F (-12°C)
High Temperature Resistance	Oven Exposure	250°F (121°C)
Chemical Resistance (Solvent)	Solvent immersion	Medium
Flame Spread*	UL 723/ASTM E-84	5
Smoke Generated*	UL 723/ASTM E-84	0

*UL File No. R6131

SURFACE PREPARATION: The surface to which the tape is applied should be dry, clean, and free of contaminants.

STORAGE CONDITIONS: Tape should be stored in a dry area at temperatures of 60°F (16°C) to 80°F (26°C).

NOTE: All physical properties listed above have been obtained from random laboratory testing and should not be used for the purpose of writing specifications. THE PRODUCT SHOULD BE TESTED TO DETERMINE THE SUITABILITY FOR ITS INTENDED USE.

Sheet No.:PIS-649

Revision No.:0.0

Date:08/01/05

