



Where innovative ideas take hold.

**#905  
4 MIL ACRYLIC ADHESIVE  
TRANSFER TAPE**

**Product Information**

**PRODUCT:**

Compac #905 is a 4 mil Acrylic Transfer Tape.

**PRINCIPAL USES:**

Compac #905 is a thicker version (4 mil) Compac #900. This product can be used for mounting, laminating, and bonds to many irregular or textured surfaces. This thick adhesive transfer tape is especially useful on foam and cloth substrates where gap filling is necessary.

**FEATURES/BENEFITS:**

Compac #905 offers a high initial adhesion, good sheer holding power, and ease of slitting.

Please contact Technical Service for help with product and application questions at 877-5COMPAC (1-877-526-6722).

TECHNICAL DATA	TEST METHOD	VALUE
Adhesive	N/A	Acrylic
Tape Thickness without Liner	PSTC-33 ASTM D3652	4.0 mils (0.10mm)
Liner	N/A	Heat and Moisture Stable Silicone Coated Paper
Color	Visual	Clear
Adhesion to Steel	PSTC- 1 ASTM D3330	72 oz/inch (79N/100mm)
Low Temperature Application	Temperature Exposure	10°F (-12°C)
High Temperature Resistance	Temperature Exposure	250°F (121°C)
Chemical Resistance (Solvent)	Solvent immersion	Medium-High

**SURFACE PREPARATION:** The surface to which the tape is applied should be dry, clean, and free of contaminants.

**STORAGE CONDITIONS:** Tape should be stored in a dry area at temperatures of 60°F (16°C) to 80°F (26°C).

**NOTE:** All physical properties listed above have been obtained from random laboratory testing and should not be used for the purpose of writing specifications. THE PRODUCT SHOULD BE TESTED TO DETERMINE THE SUITABILITY FOR ITS INTENDED USE.

Sheet No.:PIS-650

Revision No.:0.0

Date:08/01/05

