



Where innovative ideas take hold.

#906
4 MIL ACRYLIC ADHESIVE
TRANSFER TAPE

Product Information

PRODUCT:

Compac #906 is a 4 mil Acrylic Transfer Tape.

PRINCIPAL USES:

Compac #906 can be used as a laminating adhesive for foams, fabrics, metal or plastic nameplates, and is an excellent product for splicing of films, fabrics and foils. It is also suited for joining materials with irregular or textured surfaces.

FEATURES/BENEFITS:

Compac #906 offers extremely high adhesion and good shear strength. The 4 mils of acrylic adhesive have excellent gap filling properties and exhibits good adhesion to polyester and polyether foams.

Please contact Technical Service for help with product and application questions at 877-5COMPAC (1-877-526-6722).

TECHNICAL DATA	TEST METHOD	VALUE
Adhesive	N/A	Acrylic
Tape Thickness without Liner	PSTC-33 ASTM D3652	4.0 mils (0.10mm)
Liner	Weight Per Area	60 lb. Basis Weight Moisture Stable Liner
Color	Visual	Clear
Adhesion to Steel	PSTC- 1 ASTM D3330	100oz/inch (110N/100mm)
Low Temperature Application	Temperature Exposure	10°F (-12°C)
High Temperature Resistance	Temperature Exposure	250°F (121°C)

SURFACE PREPARATION: The surface to which the tape is applied should be dry, clean, and free of contaminants.

STORAGE CONDITIONS: Tape should be stored in a dry area at temperatures of 60°F (16°C) to 80°F (26°C).

NOTE: All physical properties listed above have been obtained from random laboratory testing and should not be used for the purpose of writing specifications. THE PRODUCT SHOULD BE TESTED TO DETERMINE THE SUITABILITY FOR ITS INTENDED USE.

Sheet No.:PIS-651

Revision No.:0.0

Date:08/01/05

