



Where innovative ideas take hold.

**#935**  
**3 MIL SCRIM REINFORCED**  
**ACRYLIC ADHESIVE**  
**HIGH PERFORMANCE**  
**TRANSFER TAPE**  
**Product Information**

**PRODUCT:**

Compac #935 is a scrim reinforced 3 mil Acrylic Transfer Tape.

**PRINCIPAL USES:**

Compac #935 may be used for bonding and laminating of metal, plastic and foam substrates, especially when one or both of the surfaces are rough or irregular.

**FEATURES AND BENEFITS:**

Compac #935 offers very high adhesion to most materials including difficult to bond surfaces such as polyethylene and polypropylene. Compac #935 also has a good UV and aging resistance. The scrim reinforcement allows laminated parts to be easily cut while the thick adhesive mass provides excellent gap filling properties.

Please contact Technical Service for help with product and application questions at 877-5COMPAC (1-877-526-6722).

TECHNICAL DATA	TEST METHOD	VALUE
Substrate	N/A	Synthetic Fiber Scrim
Adhesive	N/A	Acrylic
Tape Thickness without Liner	PSTC-33 ASTM D3652	3.0 mils (0.08mm)
Liner Thickness	PSTC-33 ASTM D3652	3.0 mils (0.08mm)
Color	Visual	Clear
Adhesion to Steel	PSTC- 1 ASTM D3330	70 oz/inch (77N/100mm)
Tensile Strength	PSTC-31 ASTM D3759	6 lbs/inch (MD) (105N/100mm)
Elongation	PSTC-31 ASTM D3759	30%

**SURFACE PREPARATION:** The surface to which the tape is applied should be dry, clean, and free of contaminants.

**STORAGE CONDITIONS:** Tape should be stored in a dry area at temperatures of 60°F (16°C) to 80°F (26°C).

**NOTE:** All physical properties listed above have been obtained from random laboratory testing and should not be used for the purpose of writing specifications. THE PRODUCT SHOULD BE TESTED TO DETERMINE THE SUITABILITY FOR ITS INTENDED USE.

Sheet No.:PIS-653

Revision No.:0.0

Date:08/01/05

