



Compac FM-132B

**Double-Coated
PE Foam Tape**

Product Information

Where innovative ideas take hold.

PRODUCT DESCRIPTION

PRODUCT:

Compac FM-132B is a double-coated black polyethylene foam tape (6 PCF) with rubber adhesive.

PRINCIPAL USES:

This product is designed as a high performance tape for window glazing, mounting and joining to nameplates, plastic trims, mirrors and emblems.

FEATURES/BENEFITS:

This tape features excellent adhesion to most surfaces, excellent humidity resistance, and exceptional shear performance.

Please contact Technical Service for help with product and application questions at 877-5COMPAC (1-877-526-6722).

TECHNICAL INFORMATION	TEST METHOD	VALUE
Adhesive	N/A	Synthetic rubber
Tape Thickness without liner	PSTC-33 ASTM D3652	1/32 inch (0.8 mm)
Adhesion to Steel (initial)	PSTC-1 ASTM D3330	125 oz./in.(137N/100mm)
Shear Strength(1"x1"x2 kg.)	PSTC-7 ASTM D3330	>240 hours
Liner type	N/A	60# white glassine paper
Liner thickness	PSTC-33 ASTM D3652	3.5 mils (0.09 mm)
Operation Temperature	Freezer/Oven	14°F(-10°C) to 180°F(82°C)

APPLICATION AND STORAGE:

Surface to which tape will be applied must be clean and dry, and free of contaminants. Apply pressure with plastic squeegee. Ideal storage conditions are 60°F to 80°F (16°C to 27°C), with low humidity.

This Product Information Sheet is not intended to serve as a specification for the product. For purposes of setting specification requirements, prior agreement between Compac and the user must be established. Some values shown herein are based on measures of central tendency, and as such are considered typical or average results. Other statistical measures may be employed to determine minimum or maximum specification values. Information is subject to change without notice. No warranty is expressed or implied with the information contained herein. Please review Compac Terms and Conditions of Sale for further information.

PIS:694

Revision No.: 0.0

Date: 3/11/2008

COMPAC CORPORATION · 103 Bilby Road · Hackettstown · New Jersey 07840
908/498-0660 · 800/631-9350 · Fax 908/850-0272
www.compaccorp.com · customer_service@compaccorp.com

