

Where innovative ideas take hold.

## PRODUCT DESCRIPTION

### PRODUCT:

Compac NW-2415T is a 2.4 oz. tan spun laced polyester tape coated one side with a pressure sensitive acrylic adhesive.

### PRINCIPAL USES:

Compac NW-2415T is designed as a breathable medical tape. Typical applications would include TENS and stress electrodes plus protective pads and covers.

### FEATURES/BENEFITS:

Compac NW-2415T offers good peel adhesion. It is coated with a hypoallergenic adhesive for sustained contact with the human skin.

Please contact Technical Service for help with product and application questions at 877-5COMPAC (1-877-526-6722).

TECHNICAL INFORMATION	TEST METHOD	VALUE
Carrier	N/A	Tan spun laced polyester
Adhesive	FTIR	Acrylic
Tape Thickness	PSTC-33 ASTM D-1000	16 mils (0.04 mm)
Adhesion to Steel	PSTC-3 ASTM D 1000	84 oz./in (93 N/25 mm)
72 °F Shear Strength	PSTC-7 ASTM D-3654	20 minutes
Release Liner	PSTC-33 ASTM D 1000	65# densified Kraft paper
Liner thickness	PSTC-33 ASTM D-1000	4 mils (0.01 mm)

## APPLICATION AND STORAGE:

Surface to which tape will be applied must be clean and dry, and free of contaminants. Apply pressure with plastic squeegee. Ideal storage conditions are 60°F to 80°F (16°C to 27°C), with low humidity.

*This Product Information Sheet is not intended to serve as a specification for the product. For purposes of setting specification requirements, prior agreement between Compac and the user must be established. Some values shown herein are based on measures of central tendency, and as such are considered typical or average results. Other statistical measures may be employed to determine minimum or maximum specification values. Information is subject to change without notice. No warranty is expressed or implied with the information contained herein. Please review Compac Terms and Conditions of Sale for further information.*